



**MioWORK**  <sup>TM</sup>

# A310-A330-A335

## Handheld rugged enterprise computing

The MioWORK A330 series\* are high performance handheld enterprise tablets. Featuring an IP54 ingress-resistant housing and 1 metre drop resistance, the A330 series is ready for business. Workflows are optimised through the 5.7" daylight-viewable capacitive touchscreen.

The integrated 1D or 2D/1D barcode scanner\* and programmable hotkeys allow faster accuracy for key functions and applications. The A330 series includes dual-band WiFi for use on 5GHz enterprise networks, as well as NFC/HF RFID for secure authentication.

The integrated 3G connectivity means field workers are always connected. With up to 8 hours battery life and optional rapid-charging power/data cradles, the A330 series offers uninterrupted use.



- **Unified communication**  
Redundant connectivity with 3G,  
WiFi and Bluetooth® 4.0 connected



- **Open & flexible**  
Uses Android™ 4.2.2 / 5.1 with  
SDK and emulator support  
Multi-touch 5.7" screen



- **IP54 sealed**  
- Robust design  
- Water, dust and 1m  
drop resistant



- **Integrated data capture**  
NFC, HF RFID and  
1D/2D barcodes built  
into workflows





## Specifications

### A310

### A330

### A335

Display	5.7" (HD) TFT colour LCD (720x1280), 450 nits		
Touch Panel	Capacitive multi-touch panel		
Platform	TI OMAP4470, 1.5GHz		
OS	Android 4.2.2 / Android 5.1**		
Memory	1GB RAM/16GB ROM		
Expansion	MicroSD up to 64GB		
Wireless Interface	Wireless WAN Data		
	Security: IEEE 802.1x, WEP, WPA PSK with TKIP, WPA2 PSK with AES		
	3G, Wireless 802.11 a/b/g/n (2.4 & 5GHz)		
	Bluetooth® 4.0		
	GPS		
Sensors	Accelerometer – auto rotation		
BCR	N/A	1D: Opticon: MDL-2001	1D: Opticon: MDL-2001 2D Code: CR8000
Camera	Front: 1.2M FF; Rear 5M AF with flash LED		
Physical Interface	microSIM card slot		
	microSD slot		
	mini USB-B 2.0		
	32 pogo pins (charging & USB host only), for cradle		
	Build-in mic		
	Build-in speaker		
	Headset jack		
	Power DC-jack		
Buttons	Power, volume up/down (volume up enables BCR function)		
Battery	3000 mAH Lithium-Ion battery (rechargeable) - Battery life up to 8 hours		
	LED Indicator		
Environment	IP54 and 1m drop resistant		
	-10°C to 50°C operating temperature		
	-20°C to 60°C storage temperature		
	Humidity: 0~90%, Non-Condense		
Standard Accessory	Altitude: Operating: 0~10,000ft (3000m)		
	Power adapter with power cord (UK, EU)		
	USB to mini USB cable		
Certification	CE/CB, IP54		
Warranty	12 months (extended warranty available)		
Weight	370g		
Dimensions	200x99x15mm		

#### Available accessories:

AC Mains charger; Single cradle inc. AC power pack; Multi-unit cradle inc.  
AC power pack (6); USB Cable; HDMI to mini HDMI or micro HDMI  
output cable; Hand Lanyard (pack of 5); Protective case; Screen  
Protectors; Hand Strap;

\*A310 = No barcode reader;  
A330 = 1D barcode reader;  
A335 = 1D/2D barcode reader

\*\* Not available on all models, please contact us for more  
information about Android 5.1 compatibility