

Outdoor Cabin Camera

IP Cabin Camera

GPCL-029A2GN

Features

- 1/2.7" 2MP CMOS Sensor
- Up to 1920x1080
- Support 60fps@1280x0720
- Support RTSP, OnVIF
- Support PoE
- **IP 68 rated**
- **Nitrogen filled-in**
- **850nm 4 Power IR LED**
- Built-in MIC(Optional)



Specification

CAMERA	
Lens	2.9mm
Image Sensor	1/2.7" 2.1Megapixel Progressive CMOS Sensor
Number of Effective Pixels	1920(H) x 1080(V) approx. 2.0M pixels
Min. Illumination	Color Mode: 0.2 Lux
	B/W Mode: 0.02 Lux
Scanning Mode	Progressive Scan
Day and Night Mode	Automatic, Day, Night, 8 IR LED
Auto Exposure Mode	Automatic, Manual
Shutter Speed Control	1/25 ~ 1/10,000
Auto White Balance Mode	Automatic, Manual
Digital Zoom	Yes by on-screen
Back Light Compensation	OFF/HLC/BLC/WDR(<30FPS)
DNR	OFF/LOW/MIDDLE/HIGH
Image Effect	Mirror, Flip
Privacy Mask	1 Area Selection
Video Motion Detection	1 Area Selection (8 *10=80 AREA)
Lens Shading	ON/OFF
ACE	OFF/LOW/MIDDLE/HIGH
Motion	ON/OFF
Audio	G.711

NETWORK	
Video Compression	H.264(Base line profile), MJPEG
Video Resolution (30fps@1920*1080P)	H.264 - Primary : 1920 x1080, 1280x720, 640x480, 320x240
	H.264 secondary 640x480, 320x240
Video Resolution (60fps@1280*720P) (WDR not used)	H.264 - Primary : 1280*720P, 640x480, 320x240
	H.264 secondary 640x480, 320x240
Video Streaming	H.264/H.264 or H.264/MJPEG Dual Streaming
Login Authority	Administrator, Operator, Viewer
Security	ID/Password
Network Time Sync	Synchronize Computer/NTP Server, Manual
Remote Upgrade	Using Web Browser
Protocols	TCP/IP, UDP, IPv4, HTTP, UPnP, RTP, RTSP, RTCP, DHCP
Client Software	Built-In Web, ONVIF Compatible 3rd Party VMS
Max. User Connection	4 Users
SDK Support	CGI Command, ONVIF Compliant
OPERATION ENVIRONMENTS	
Operating Humidity	0~80% (non-condensing)
Operating Temperature	-10°C ~ +60°C
PoE	Support
DC12V	Optional
Power Consumption	1.6W

Dimension

