





Separate camera unit with high sensitivity image sensor

The DrivePro Body 52 is comprised of a main unit and a separate, compact camera unit which can be securely mounted on uniforms and vests for more flexible wearing options. The camera features a wide 130° horizontal field of view, a large f/1.8 aperture, and a Sony Exmor™ Sensor for high-resolution images with superb, rich color even in low light conditions.



Mounting accessories included

All necessary mounting accessories are included with the DrivePro Body 52.
Officers can choose to use either the 360° rotating clip or Velcro holder to mount the camera unit on their uniform or jacket, and use the belt holster to carry the main unit on their duty belt.



Quick snapshot button

The DrivePro Body 52's quick snapshot button allows users to take photos while recording video simultaneously. During an incident, just reach up and discreetly press the snapshot button to capture photographic evidence on the spot.





Body Cameras

DrivePro™ Body 52

Features

- · High sensitivity image sensor
- F/1.8 aperture and 130° viewing angle for clear and smooth 1080P recordings
- · Built-in Wi-Fi function for live streaming
- · Quick snapshot button
- 360° rotatable clip, Velcro holder and belt holster included

Transcend

DrivePro Body Toolbox

Transcend's DrivePro Body Toolbox is exclusively designed for the DrivePro Body series, featuring a user-friendly interface that allows users to securely manage recorded videos and snapshots on Windows PCs. In addition, users can adjust settings for both the toolbox and the DrivePro Body device, format the internal storage, and upgrade the body camera's firmware via the toolbox.

Specification

Α	n	n	\triangle	=	r	=	n	\sim	\mathcal{L}
$\overline{}$	U	U		u		u		•	·

Dimensions (Max.)	88.4 mm x 52.2 mm x 17.4 mm (3.48" x 2.06" x 0.68")		
Camera Dimensions (Max.)	40 mm x 40 mm x 20.35 mm (1.57" x 1.57" x 0.80")		
Weight (Max.)	84 g (2.96 oz)		
Camera Weight (Max.)	64 g (2.26 oz)		

Interface

USB Type	3.5mm plug to USB Type A		
Connection Interface	USB 2.0		

Storage

Capacity 32GB internal memory

Hardware

Viewing angle	130° (diagonal)
Aperture	F/1.8

Power

Battery Life (Fully Charged)	3.5 hour(s)
Power Supply (Max.)	Input: AC 100V-240V, 50-60Hz, 0.4A Output: DC 5V / 2A

Format

Resolution	Full HD 1080P
Frame Rate	30 fps
Video Format	MOV (H.264)

Operating Environment

Operating Temperature	-20°C (-4°F) ~ 65°C (149°F)
Storage Temperature	-25°C (-13°F) ~ 70°C (158°F)
IP Rating	IPX4

Warranty

Certificate	CE/FCC/BSMI/NCC/MIC/KC
Warranty	Two-year Limited Warranty

Ordering Information

32GB	TS32GDPB52A
------	-------------



Body Cameras Comparison













DrivePro™ Body 60

DrivePro™ Body 30

DrivePro™ Body 52

DrivePro™ Body 20

DrivePro™ Body 10

	Driverio Body 60	Driverio Body 30	Driverio Body 32	Driverio Body 20	Driverio Body 10
Appearance					
Dimensions (Max.)	95.9 mm x 52.2 mm x 24.9 mm (3.78" x 2.06" x 0.98")	95.9 mm x 52.2 mm x 27.6 mm (3.78" x 2.06" x 1.09")	88.4 mm x 52.2 mm x 17.4 mm (3.48" x 2.06" x 0.68")	88.4 mm x 52.2 mm x 19.4 mm (3.48" x 2.06" x 0.76")	88.4 mm x 52.2 mm x 19.6 mm (3.48" x 2.06" x 0.77")
Camera Dimensions (Max.)	61.3 mm x 22 mm x 22 mm (2.41" x 0.87" x 0.87")	-	40 mm x 40 mm x 20.35 mm (1.57" x 1.57" x 0.80")	-	-
Weight (Max.)	167 g (5.89 oz)	130 g (4.59 oz)	84 g (2.96 oz)	88 g (3.10 oz)	88 g (3.10 oz)
Camera Weight (Max.)	-	-	64 g (2.26 oz)	-	-
Interface					
USB Type	3.5mm plug to USB Type A	micro USB to USB Type A			
Connection Interface			USB 2.0		
Storage					
Capacity	64GB internal memory	64GB internal memory	32GB internal memory	32GB internal memory	32GB
Hardware					
Viewing angle	130° (diagonal)	130° (diagonal)	130° (diagonal)	160° (diagonal)	130° (diagonal)
Aperture	F/2.8	F/2.0	F/1.8	F/2.8	F/2.8
Sony Image Sensor	✓	✓	✓	-	✓
Infrared LEDs	-	✓	-	-	✓
Wi-Fi	~	~	✓	✓	-
Bluetooth	✓	~	-	-	-
Microphone	✓	✓	✓	✓	✓
Vibration Alert	✓	✓	-	-	-
Buffering Mode	~	✓	-	-	-
Event Recording	-	-	✓	✓	✓
Loop Recording	✓	~	~	✓	✓
Power					
Battery Life (Fully Charged)	10 hour(s)	12 hour(s)	3.5 hour(s)	3.5 hour(s)	5 hour(s)
Power Supply (Max.)	Input: AC 100V-240V, 50-60Hz, 0.4A Output: DC 5V / 2A				
Format					
Resolution			Full HD 1080P		
Frame Rate	30 fps				
Video Format	MP4 (H.264)	MOV (H.264)	MOV (H.264)	MOV (H.264)	MP4 (H.264)
Operating Environment					
IP Rating	IP67	IP67	IPX4	IPX4	IPX4
Warranty					
Warranty		T	wo-year Limited Warran	ty	
	- y				