

- Kabylake /Skylake
- Desktop
- DP
- 4K
- 6
- USB3.0
- GPU



RoHS

Features

- Intel® Kabylake/Skylake Processor
- 2 x SO-DIMM DDR3L, Up to 32GB
- 6 x DP, Supporting 4K Display
- 1 x 2.5" SATA, 1 x mSATA
- 1 x Type-C USB3.0, 1 x USB3.0, 4 x USB2.0, 2 x RS232
- 2 x RJ45, 1 x Mini-PCIe for WiFi/BT

Specifications

CPU	Intel® LGA1151 Socket 6 th /7 th Gen. Processor
BIOS	AMI Source Code
Chipset	H110
System Memory	DDR3L-1600MHz, 2 x SO-DIMM, Up to 32GB
GPU	AMD Radeon™ 7750 GPU, GDDR5 2GB
Graphic Engine	DirectX 11.1, OpenGL 4.2, OpenCL 1.2
Display Interface	3 x 2 DP Landscape Max. 5760 x 2160
Network Controller	Intel I219/I211 Gigabit Ethernet
Ethernet	2 x RJ45
USB	1 x Type-C USB3.0, 1 x USB 3.0, 4 x USB2.0
Serial Port	2 x RS232
Audio	1 x MIC-IN, 1 x AUDIO-OUT
Mini-PCIe	1 x Full-size Mini-PCIe for mSATA 1 x Full-size Mini-PCIe for WiFi/BT
Storage	1 x 2.5" SATA 1 x Full-size mSATA
JAHC	WatchDog Timer Auto Power On RTC Remote Control
Operation System	Windows 7/8.1/10 (64-bit)/Linux
Power Requirement	AC/110V~220V
Dimensions (W x D x H)	350mm x 235.2mm x 43mm (13.78" x 9.26" x 1.69")
Construction	Metal
Mounting (Optional)	Wall Mounting and VESA Mounting Kit (JZ300)
Color	Black
Operating Temperature	0°C ~ 40°C (32 °F ~ 104 °F) at 0.7m/s Air Flow
Relative Humidity	95% @ 40°C (non-condensing)
Certification	CE, FCC Class B, CCC

Order Information

G330-B0000	Intel® LGA1151 Socket 6 th /7 th Gen. Processor GPU: AMD Radeon™ 7750 GPU, DDR5 2GB Dram
Packing List	2 x WiFi Antenna, 1 x Drive Disk, 1 x User Manual, 1 x AC Power Cable
Optional Item	VESA Mounting Kit (JZ 300)

Dimensions and Drawing

