# Open Frame LCD



## 12.1"(16:10)


RoHS COMPLIANT 2002/95/EC

### Specifications

| | |
|---|---|
| Model Name | W12L100-OFM5 |
| Viewable Size Image | 12.1"(16:10) |
| Active Display Area(mm) | 261.12(H)x163.2(V) |
| Pixel Pitch(mm) | 0.204mmX0.204mm |
| Number of Pixels | 1280x800 |
| Contrast Ratio | 600:1(typ.) |
| Display Color | 262,144(6bits/color) |
| Brightness(cd/m ) | 500(typ.) |
| Viewing Angle(CR>=10) | -80~80(H);-80~80(V) |
| Synchronization Range Horizontal/Vertical | 31.5~60.0KHz/60~75Hz |
| Recommended Resolution | 1280x800@ 60Hz |
| Signal Connector | 15 pin D-sub |
| Power Source | AC100~240V, Universal, ±10% |
| Power Consumption | 20W typical, normal operation |
| Power Management | VESA DPMS Compliant |
| Plug & Play | VESA DDC 1/2B |
| Optional Video Input | S-Video, Composite |
| Optional DVI Input | No |
| Optional Touch Screen | 4 W Resistive |

Remarks:W12L100series= VGA Input only
W12L110series= VGA+Video Input

### Mechanical Drawing




UNIT:mm

* Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.