

Kabylake /Skylake

Desktop

2xHDMI

10xUSB

M.2



RoHS  

Specifications

CPU	Intel® LGA1151 Socket 6 th /7 th Gen. Processor
BIOS	AMI Source Code
Chipset	H110
System Memory	2 x SO-DIMM DDR3L Memory, Up to 32GB
GPU	Intel® HD Graphics 520/620
Graphic Engine	Direct3D 2015, OpenGL 4.5, OpenCL 2.1
Display Interface	1 x HDMI1.4b (Max. 3840 x 2160 @30Hz) 1 x HDMI2.0 (Max. 3840 x 2160 @60Hz)
Network Controller	Intel® I219LM Gigabit Ethernet
Ethernet	1 x RJ45
USB	4 x USB 3.0, 6 x USB2.0
Serial Port	1 x RS232
Audio	1 x MIC-IN, 1 x AUDIO-OUT
M.2	1 x M.2 (2242/2280) for SSD 1 x M.2 (2230) for WiFi/BT
Storage	1 x 2.5" SATA
JAHC	WatchDog Timer Auto Power On RTC
Operation System	Windows 7/8.1/10 (64-bit)/Linux
Power Requirement	DC-IN/19V/4.74A
Dimensions (W x D x H)	180mm x 177mm x 36mm (7.09" x 6.97" x 1.42")
Construction	Metal
Mounting (Optional)	VESA Mounting (JZ300)
Color	Black
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F) at 0.7m/s Air Flow
Relative Humidity	95% @ 40°C (non-condensing)
Certification	CE, FCC Class B, CCC

Features

- Intel® Core Skylake-S/Kabylake-s Series Processors
- 2 x SO-DIMM DDR3L Memory, Up to 32GB
- 1 x HDMI1.4b, 1 x HDMI2.0
- 1 x 2.5" SATA, 1 x M.2 (2242/2280) for SSD
- 4 x USB3.0, 6 x USB2.0, 1 x RS232,
- 1 x RJ45, 1 x M.2(2230) for WiFi/BT

Order Information

BQ67-H110	CPU: Intel® LGA1151 Socket 6 th /7 th Gen. Processor
Packing List	2 x WiFi Antenna, 1 x Drive Disk, 1 x User Manual, 1 x AC Power Cable, 1 x AC Power Adapter
Optional Item	VESA Mounting Kit (JZ 300)

Dimensions and Drawing

