

M3070

21.5" All In One System

Intel 8th core i

















- 21.5" Full HD TFT LCD with 30,000 hrs backlight lifetime
- True-flat touchscreen with projected capacitive multi-touch control
- High-quality stereo sound

Introduction

Maestro 3070 AIO is an elegant all-in-one PC, powered by latest Intel Coffee Lake platform for best computing and graphic performance along with Windows 10 compatibility. Features like 21.5" Full HD panel, 10 point touch screen, high-quality stereo sound output, these are also all aiming at fulfilling all of your PC demands in different user scenarios, whether in your business or at home.

Not only feature-rich, Maestro 3070 are also designed to delivery the best flexibility and user-friendly experience to let user can very easily access the internal system for DIY or component upgrade. All of these to make Maestro 3070 maximize all your desires on PC in one.




I/O Interface





- 1 ODD
- 2 Card Reader
- 3 USB 2.0
- 4 DC-in
- **5** USB 3.0
- **6** Display Port
- 7 HDMI
- 8 Giga LAN
- USB 3.0
- 10 Line-out
- Mic-in

Dimension (mm)









M3070

Commercial Panel PC

LCD						
Display Type		21.5" TFT-LCD				
Max. Resolution		1920 x 1080				
Max. Colors		16.7M (6bit)				
Luminance		250 cd/m2				
Viewing Angle		170°/160°				
Led Backlight (Hours)		30000				
TOUCH SCREEN						
Туре		P-CAP				
Touch Screen		True-flat 10 points				
SYSTEM						
	Processor	8th Gen Intel *Coffee Lake LGA1151 Socket Processor, TDP Max. 65W				
	Chipset	H310				
	System Memory	DDR4 2666MHz, 2 x 260-pin SO-DIMM, Max. 32GB (Non-ECC)				
	Ethernet	Intel® 1219-LM Giga LAN + Intel 1210-AT Giga LAN				
	2	1 x DC Jack				
	I/O Port	4 x USB 3.0				
		1 x RJ-45				
PH12SI						
1111231		1 x DisplayPort 1.2 1 x HDMI 1.4				
		1 x Line-out , 1 x Mic-in				
	Watchdog Timer	1~255 steps by software program				
	Storage Disk Drive					
	Storage Disk Drive	1 x SATA 2.5"/3.5" HDD/SSD bay 1 x M.2 2230 E key slot *not support Intel CNVi wifi module				
	Expansion Slot	1 x M.2 2280 M key slot				
	Stereo Speaker	2 x 5W				
	OS Support	Windows 10 64bit, Linux (support by request)				
		Willdows to oabil, Elitox (support by request)				
SIDE I/O PORTS						
USB 2.0		2				
4-in-1 Card Reader		1				
ODD		DVD super-multi double layer (optional), Blu-ray ODD support (optional)				
Webcam		1.0 HD mega pixel, HD 720p 16:9 lens with array digital microphone				
System Button		Power, Brightness control				
POWER REQUIREM	MENT					
Power Input		DC 19V				
Power Adapter		AC to DC adapter				
MECHANICAL						
Mounting		VESA mount support 100mm x 100mm (optional)				
Dimension		539.5mm x 419.7mm x 199.5mm (w/ Stand)				
Weight		8.9kg (19.58 lb)				
ENVIRONMENTAL						
Operating Temperatu		0°C ~ 40°C				
Storage Temperature		-20°C ~ 60°C				
Storage Humidity		10% ~ 95% @60°C non-condensing				
Vibration Resistance		Operating Random vibration Test 5-500Hz, 0.3Grms@with HDD				
Shock Resistance		Operating 50 G peak (3 ms duration)				
EMC		CE, FCC Class B				
Front Panel Protection	1	-				

Ordering Information

System I/O										
Model Number	Chipset	DisplayPort	HDMI	USB 3.0 / 2.0 / CardReader	Line out / Mic-in	M.2 2230 E key / M.2 2280 M key	LAN	Wifi/BT	Power	
M3070-12FEI-H310-M2	H310	1	1	4/2/1	1/1	1/1	1	optional	DC-in 19V	

Industrial Panel PC