




ND62

10.1" Rugged Tablet

Product Feature



Sealing



Drop Test

MIL-STD-
810G

Certified



Tumble Test



Hot-Swap Battery



Barcode Scanner

In the Field, In the Vehicle, In the Office

- MIL-STD 810G tested, 5ft. / 1.5m drop proof.
- IP65, one-meter tumble test.
- Hot swap battery, 4800mAh / 7.6V battery pack.
- Firmware TPM 2.0.
- Gb ethernet port with PXE support for reliable communication & maintenance.
- Optional Windows® Hello camera.
- Optional vehicle dock, office dock.
- Optional digitizer, stylus, briefcase handle, hand strap.
- Optional 4G LTE multi carrier mobile broadband.
- Optional 1D/2D Honeywell barcode readers for data acquisition.



Office Dock



Battery Charger



Vehicle Dock





Specifications

SOFTWARE

DURABILITY

- Windows® 10 IoT Enterprise, Windows 11
- MIL-STD-810G (Multiple 5' / 1.5 m Drops)
- IP65
- 1m tumble test
- Steel ball drop test, 25 mm diameter steel round ball weight of 250 gm from 50cm. w/o screen protector
- Optional Glass screen protector
- Operating temp. : -10°C ~50°C
- Storage temp. : -20°C ~60°C

CPU

- Intel® Gemini lake-R Celeron N4120 (optional Pentium N5030)

STORAGE & MEMORY

- LPDDR4 8GB on board (optional 4GB)
- 128GB eMMC

DISPLAY

- 10.1", 16:10 ratio 1920x1200 IPS 800 nits Sunlight readable

AUDIO

- 2 x 2W Speaker
- 2 x Digital microphone

INPUT

- 10-point multi-touch, support glove mode and wet-touch mode
- 5 Physical buttons (power, vol+, vol-, 2 x programmable keys)
- Support MPP2.0

CAMERAS

- 2MP front camera (Win 10 Hello optional)
- 8MP rear camera, Auto Focus, Flash

WIRELESS

- GPS / GLONASS / GALILEO
- Wi-Fi 6 (802.11ax)
- Bluetooth® 5.2
- Optional Quectel EM06-E (EMEA)

SECURITY

- Firmware Trusted Platform Module (TPM 2.0)
- Kensington cable lock slot
- Optional Windows® Hello

INTERFACE

- -Docking connector
- -USB 3.1 Type A x 1
- -USB 3.1 Type C x 1
- -RJ45 Gigabit Ethernet Port
- -Replaceable DC jack
- -Micro HDMI
- -3.5mm Audio jack
- -SIM Card Reader (Nano)
- -SDXC Card Reader (Micro)
- -Reset hole

POWER SUPPLY

- Backup Battery / Hot swappable battery
- Battery: 7.6V, 4800mAh / 36.5Wh
Battery operation: up to 10 hours
- Backup Battery: 7.4V, 142mAh / 1.05Wh

DIMENSIONS & WEIGHT

- 11.1" x 7.6" x 0.6" (283mm x 192mm x 15mm)
- 990g w/o screen protector

COLLABORATION

- 9 Axis MEMS sensor (Accelerometer, eCompass, Gyroscope)
- Ambient Light Sensor
- Proximity Sensor
- Optional 1D/2D Barcode Reader

LED INDICATORS

- Power, Battery, WIFI

ACCESSORIES

- -AC Adapter 65W (19V / 3.42A)
- -Hand strap with stylus holder
- -Optional Capacitive stylus pen
- -Optional Digitizer
- -Optional Vehicle Dock
- -Optional Office Dock
- -Optional Battery Charger



Contact info

Tel +886-2-32345599

Website <https://ruggedtablet.msi.com/>

