

Philips Signage Solutions D-Line Display

43"Powered by Android 500cd/m²

SignageSolutions



43BDL4550D

Say more

Smart, fast 24/7 display.

Make it stand out with a fast Philips D-Line Professional 4K UHD display. Philips superb picture quality ensures true colors and intense contrast. You can effortlessly display content from multiple sources on a single screen.

Care about you, your business and your audience

- · Keep your content up and running with FailOver
- SmartPower for energy saving
- Ensure your content is running with automatic screenshots

Innovative solutions for any signage application

- · Save and play content with internal memory
- Integrated dual-band WiFi
- Android SoC processor. Native and web apps

Maximizing the impact of your message

- Manage settings of multiple displays with CMND & Control
- Create and update content with CMND & Create
- CMND: Take control of your displays
- · Connect and control your content via the cloud



Highlights

Internal Memory



Save and play content with internal memory. Upload your media into the display and playback content immediately. Working in conjunction with the internal browser, it also serves as a memory cache when streaming online content. If the network ever fails, the internal memory keeps content running by playing a cached version of the content, ensuring that your media stays up even if the network goes down.

CMND & Control



With CMND & Control, easily manage multiple displays in a central location. With real time display monitoring, setting and software updates from a remote location, and the ability to customize and configure multiple displays at once, such as video wall or menu board displays, controlling your suite of displays has never been easier.

CMND & Create



Design and create compelling content with CMND & Create, a powerful authoring tool. With a drag and drop interface, preloaded templates, and integrated widgets, you'll be able to amaze your customers with compelling

content. Available in portrait and landscape mode.

CMND



A robust display management platform, CMND puts the power back into your hands. Update and manage content with CMND & Create or control your settings with CMND & Control. It's all possible with CMND.

FailOver



Keeping your content up and running is critical for demanding commercial applications. While it is unlikely you will face a content disaster, FailOver provides content protection with a revolutionary technology that plays back-up content on screen in the event of a media player failure. FailOver automatically kicks in when the primary input fails. Simply select a primary input connection and a FailOver connection and your ready for instant protection.

SmartPower



The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

Powered by Android 8

Control your display via an Internet connection. Android-powered Philips Professional Displays are optimized for native Android apps, and you can install web apps directly to the display too. A new Android 8 ensures the software is kept secure and remain to the latest specification for longer.

Proof of Play

Content is king, and with the automatic screenshot feauture, you can make sure that your content is up and running at all times. Screenshots are taken throughout the day, which are then stored in the FTP server. From there, the screenshots can be viewed no matter when, or where you are.

SmartBrowser

Connect and control your content via the cloud with the integrated HTML5 browser. Using the Chromium based browser, design your content online and connect a single display, or your complete network. Show content in both landscape and portrait mode, with fullHD resolution. Simply connect the display to the internet using WiFi or with an RJ45 cable, and enjoy your own created playlists.

Specifications

Picture/Display

- Diagonal screen size: 42.5 inch / 108.0 cm
- Panel resolution: 3840 x 2160
- Optimum resolution: 3840 x 2160 @ 60Hz
- Brightness: 500 cd/m²
- Contrast ratio (typical): 1200:1
- Dynamic contrast ratio: 500,000:1
- Aspect ratio: 16:9
- Response time (typical): 8 ms
- Pixel pitch: 0.2451 x 2451 mm
 Display colors: 1.07 G Billion
- \bullet Viewing angle (H / V): 178 / 178 degree
- Picture enhancement: 3/2 2/2 motion pull down, 3D Combfilter, Motion compens. deinterlacing, 3D MA deinterlacing, Dynamic contrast enhancement, Progressive scan
- Operating system: Android 8.0
- · Panel technology: IPS

Connectivity

- Video input: Display Port1.2 (x1), DVI-I (x 1), HDMI 2.0 (x2), USB 2.0 (x2)
- Video output: DisplayPort 1.2 (x1), HDMI 2.0 (x1)
- Audio input: 3.5 mm jack
- Audio output: 3.5mm jack
- External control: RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack
- WiFi: dual antenna 2,4Ghz and 5Ghz

Supported Display Resolution

Computer formats

Resolution Refresh rate 1920 x 1080 60Hz 1024×768 60Hz 1280×1024 60Hz 1280×720 60Hz 1440×900 60 Hz 1600 x 900 60Hz 1680 × 1050 60Hz 3840×2160 30. 60Hz 640×480 60Hz 800×600 60Hz

• Video formats

Resolution Refresh rate 50, 60Hz 1080i 576i 50Hz 576p 50Hz 480p 60Hz 60Hz 480i

1080p 50. 60Hz 24, 30, 60Hz 2160p 720p 50,60 Hz

Dimensions

- Set dimensions (W \times H \times D): 973.0 x 561.2 x 63.5 mm
- Set dimensions in inch (W x H x D): $38.31 \times 22.09 \times 2.50$ inch
- Bezel width: 13.9 mm (Even bezel)
- Product weight (lb): 23.61 lb
- Product weight: 10.71 kg
- Wall Mount: 200 (H) x 200(V) mm, M6

Convenience

- Placement: Landscape (24/7), Portrait (24/7)
- Tiled Matrix: Up to 10 x 15
- · Keyboard control: Hidden, Lockable
- · Signal loop through: RS232, IR Loopthrough, DisplayPort, HDMI
- Network controllable: RS232
- Energy saving functions: Smart Power
- · Screen saving functions: Pixel Shift, Low Bright
- WiFi protocol: a b g n, 802.1x

Power

- Standby power consumption: <0.5 W
- Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz
- Consumption (Typical): 83 W
- Consumption (Max): 123 W
- · Energy Label Class: G

Operating conditions

- Temperature range (operation): 0 ~ 40 °C
- Temperature range (storage): -20 \sim 60 °C Altitude: 0 \sim 3000 m
- MTBF: 50,000 hour(s)
- Humidity range (operation)[RH]: 20 80% RH (No condensation)
- Humidity range (storage) [RH]: 5 95% RH (No condensation)

• Built-in speakers: 2 x 10W RMS

Accessories

• Included accessories: Quick start guide, RS232 cable, AC Power Cord, IR sensor cable (1.8M), Remote Control & AAA Batteries

- Stand: BM05922 (Optional)
- Included Accessories: AC Switch Cover, Philips logo (x1), RS232 daisy-chain cable, Screws, USB Cover (x1)

Multimedia Applications

- USB Playback Audio: AAC, HEAAC, MPEG
- USB Playback Picture: BMP, JPEG, PNG
- USB Playback Video: MPEG, H.263, H.264, H.265

Miscellaneous

- On-Screen Display Languages: English, French, German, Spanish, Polish, Turkish, Russian, Italian, Simplified Chinese, Traditional Chinese, Arabic, Japanese, Danish, Dutch, Finnish, Norwegian, Portuguese, Swedish
- Regulatory approvals: CE, CCC, RoHS, BSMI, CB, VCCI, CU, EMF, EnergyStar 8.0, ETL, FCC, Class A. PSB
- Warranty: 3 year warranty

Internal Player

- CPU: 2 x A53 + 2 x A73
- GPU: ARM Mali G51
- Memory: 3GB DDR
- Storage: 32 GB eMMc



Issue date 2022-07-14

Philips 43BDL4550D

© 2022 Koninklijke Philips N.V. All Rights reserved.

Version: 2.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 68904 EAN: 87 12581 76919 2

www.philips.com