



FPC-1736

17" 8th/9th Gen Intel® Generation Core™ Pentium® i7/ i5/ i3 Processors Full-falt Rugged Multi-touch Panel PC With Active Cooling and Expansion Slot

- > Intel® LGA1151 Socket Supports 8th /9th refresh Generation Core™ Pentium® i7/ i5/ i3 Processors (Max. TDP at 65W)
- > 2 x Memory Socket, Max. Up to 64GB DDR4 2133/2400/2666 MHz
- > 4 x USB3.0, 1 x USB2.0 (Internal for dongle)
- > 3 x RS232, 2 x LAN, 1 x HDMI 1.4b, 1 x VGA
- > 1 x Storage, 2.5" Drive Bay, 1 x M.2 SSD
- > 1 x M.2 Key-E for Wi-Fi, Bluetooth
- > Support 1 x PCIe4 Expansion Slot (option for 2 x PCI slot)
- > Wide Voltage DC input +12V ~ +24V
- > Front IP65, Panel Mounting Kits
- > CE, FCC Class A, CCC

+ Spec

-System Information-	
Processor	Intel® LGA1151 Socket Supports 8th /9th refresh Generation Core™ Pentium® i7/ i5/ i3 Processors (Max. TDP at 65W)
Platform Controller Hub	Intel® H310 Express Chipset
System Memory	2 x 260-pin DDR4 2666 MHz SO-DIMM socket, supports up to 64GB Max
I/O Chipset	ITE8786E
BIOS Information	AMI uEFI BIOS, 128Mbit SPI Flash ROM
Board	EMX-H3102C
Expansion	
Expansion	1 x M.2 E-Key, support Wi-Fi module (optional) 1 x PCIe4 slot (Option for 2 x PCI slot)
Storage	
Storage	1 x SATA III for SSD expansion 1 x M.2 B-key 2242 slot support SATA
Panel	
LCD Size	17", 4:3
Display Type	SXGA
B/L Inverter/Converter	External
Resolution	1280 x 1024
Pixel pitch	0.264(H) x 0.264(V)mm
Luminance	250 nits
Contrast ratio	1000
Viewing angle	80 (U), 80 (D), 85 (L), 85 (R)
Response time	5ms
Backlight	LED
Touch Screen	17" PCAP Multi-Touch support up to 10 points
Touch Light Transmission	89 %
Touch Controller	ILLITEK IC12510P
I/O	
USB Port	4 x USB3.0, 1 x USB2.0 (Internal Type A for dongle) 4 x USB2.0 (Option)
COM Port	3 x RS232, 1 x RS232 (Option)
GPIO	8 bit GPIO (option)
Antenna	Reserved for WIFI6 2.4GHz~7.1GHz Antenna
SATA	1 x SATA III
PCIe	1 x PCIe4 (Option for 2 x PCI slot by module)
Wireless Communication	
WLAN	IEEE802.11 ax/ac/a/b/g/n 2.4 GHz, 5GHz, 6GHz (Option)
Bluetooth	BT5.2 (Option)
Display	
Graphic Chipset	Intel® 8/9th Generation CPU integrated
Spec. & Resolution	1 x VGA: 2048 x1536 @ 50 Hz 1 x HDMI 1.4b: 4096x2160@30Hz
Audio	
Audio Interface	1 x Line-out, 1 x Mic-in
Speaker Output	2 x 5W
支持软件	
OS	Windows 10 64bits Linux (Ubuntu 22.04)
Certifications	
Certification Information	CE/FCC Class A CCC
Ethernet	



LAN Chipset	1 x Intel i219-V Gigabit Ethernet 1 x Intel i225-V 2.5 Gigabit Ethernet
LAN Port	2 x RJ-45
Power Requirement	
DC Input	+12~24V DC in
DC Input Connector	DC in Phoenix terminal (option) *Only connect one of them for power input
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 120W (24V @ 5A) AC-DC Power adapter
Mechanical & Environmental	
Operating Temperature	0 ~ 45°C
Storage Temperature	-20°C ~ 60°C
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Dimension (W x L x H)	392.72 x 325.32 x 121.55 mm
Weight	7.5 Kg
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
IP Rating	Front IP65
VESA	Wall / Stand / VESA , 100mm x 100mm
System Fan	2 x 12V
Construction - Front	Die-casting
Construction - Rear	Metal
Drop	ISTA 2A, IEC-60068-2-32 Test:Ed
Ordering Information	
Ordering Information	FPC-1736-X0000-1R 17" 1280x1024 250nits Industrial Touch Panel PC, ErP Design, PCAP Multi Touch(ALC897) Intel w/H310/2LAN/4USB3/HDMI/VGA/DCin/Line out/Mic in/Barebone/120W Power adapter w/PClex4 expansion slot ACC-CPU-8700TR Intel Core i7-8700T 2.4GHz Processor ACC-CPU-8500TR Intel Core i5-8500T 2.1GHz Processor ACC-CPU-8100TR Intel Core i3-8100T 3.1GHz Processor C971XFP1736000R Double USB KIT For FPC-1736 C971XFP1736001R Single USB KIT For FPC-1736 C971XFP1736002R Internal Single USB KIT For FPC-1736 C971XFP1736003R 4Terminal Block DC IN KIT For FPC-1736 C971XFP1736004R Terminal Block GPIO KIT For FPC-1736 C971XFP1736005R WiFi module KIT for FPC-1736 Intel AX210 C971XFP1736006R Riser card KIT For FPC-1736 PClex1 to 2PCI Riser Card C971XFP1736007R WiFi module KIT for FPC-1736 IntelAC8265 C971XFP1736008R WiFi module KIT for FPC-1736 IntelAC9260 C971XFP1736008R CPU cooler 4P/12V/Fan/84*84*28/AL/65W C971XFP1736008R CPU Cooler for LGA1155 Package 4-Pin/12V C170P060040R US Power Cord SM001/3P+SM006/3P 1.83M C170P060050R EU Power Cord SH005/3P+SH006/3P 1.83M C170P060060R JP Power Cord SH001/3P+SH006/3P 1.83M C170P060070R UK Power Cord YP61A/3P+YC12/3P 1.83M C170P060080R AU Power Cord SH051/3P+SH006/3P 1.83M