

<Color TFT-LCD Module >

AA175TE03

17.5 inch WXGA FOR INDUSTRIAL USE

AA175TE03



FEATURES

Super Wide Viewing Angle (-85~85° H,V) High Contrast Ratio 1000:1 LED Lifetime 100,000h(Typ.) *1), *2)

- * 1) LED life time is defined as the time when the brightness becomes 50% of the initial value.
- *2) The life time of the backlight depends on the ambient temperature. The life time will decrease under high temperature.

SPECIFICATION

| ITEM | SPECIFICATION |
|-------------------------------|--|
| Display Area (mm) | 380.2 (H) × 228.1 (V) (17.5-inch diagonal) |
| Number of Dots | $1280 \times 3 \text{ (H)} \times 768 \text{ (V)}$ |
| Pixel Pitch (mm) | 0.297 (H) × 0.297 (V) |
| Color Pixel Arrangement | RGB vertical stripe |
| Display Mode | Normally black |
| Number of Color | 262k(6 bit/color), 16.7M(8 bit/color) |
| Luminance (cd/m²) | 450 |
| Viewing Angle ($CR \ge 10$) | -85~85° (H), −85~85° (V) |
| Surface Treatment | Anti-glare and hard-coating 3H |
| Electrical Interface | LVDS (6 bit/8 bit) |
| Module Size (mm) | 404.0 (W) × 258.0 (H) × 16.2 (D) |
| Module Mass (g) | 1570 |
| Backlight Unit | LED, edge-light, replaceable |

Characteristic value without any note is typical value.

Keep safety first in your circuit designs!

Mitsubishi Electric Corporation puts the maximum effort into making LCD products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with LCD may lead to personal injury, fire or property damage. Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of non-flammable material or (iii) prevention against any malfunction or mishap.

Notes regarding these materials

- •These materials are intended as a reference to assist our customers in the selection of the Mitsubishi LCD product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Mitsubishi Electric Corporation or a third party.
- •Mitsubishi Electric Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
- •All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Mitsubishi Electric Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact Mitsubishi Electric Corporation or an authorized Mitsubishi LCD product distributor for the latest product information before purchasing a product listed herein.
- The information described here may contain technical inaccuracies or typographical errors. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.
- Please also pay attention to information published by Mitsubishi Electric Corporation by various means, including the Mitsubishi Semiconductor home page (http://www.MitsubishiElectric.com/).
- •When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
- •Mitsubishi Electric Corporation LCD are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi LCD product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
- •The prior written approval of Mitsubishi Electric Corporation is necessary to reprint or reproduce in whole or in part these materials.
- •If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.
- Any diversion or re-export contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
- •Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi LCD product distributor for further details on these materials or the products contained therein.